

LIGHTS

9470

Remote Area Lighting System

Call Engineered Packaging Solutions for more information and pricing at 1-800-592-7406



9470 Remote Area Lighting System

Using solid-state mounted LED's coupled with a thermally efficient light engine and our [1610 Pelican Protector™ Case](#), the RALS 9470 gives the user the ultimate maintenance free portable floodlight station to get the job done efficiently, safely and on time. The RALS 9470 houses all four of it's light heads and it's multi-stage charger for that total self contained convenience, it is also equipped with a telescopic handle and rugged wheels for ease of transport.

Comes with convenient low battery warning system and waterproof activation switch.

CAUTION: The Pelican Products RALS models 9450, 9460 and 9470 contain sealed lead acid batteries that can generate hydrogen gas when charging. It is imperative that these products are charged, as instructed, with the case lid open to allow any gases to escape as charging with the lid closed poses a significant hazard. Failure to abide by this instruction could result in injury and/or damage to property. Please refer to the warnings provided in the instructions for the unit and on a decal affixed to the inside of the case adjacent to the cavity where the charger unit is packed.

9470 Remote Area Lighting System Configurations

Cat. #	Description
9470	9470 Remote Area Lighting System



9470 Remote Area Lighting System Specifications

Light Source

LED Type	LED Life	Tested Lumen Value
High Flux LED	50000 hrs.	4000 (Low) 8000 (High)

Lamp Heads	Number of LEDs	Beam Spread
4	24 LEDs per head	90°

Brightness Settings
2

Power Source

Battery Type	Battery Burn Time	Battery Charging Time
12v Rechargeable, Sealed	14 hrs. (Low) 7 hrs. (High)	8 hrs. from full discharge

Battery Life	Low Battery Warning	12V Primary Sockets
2000 cycles	Intermittent Blinking	4

12V Auxiliary Sockets	Watts	Voltage
1	96	12

Dimensions & Weight

Head Length	Head Width	Head Depth
6.5" (16.5 cm)	7.87" (20 cm)	2.56" (6.5 cm)

Width Closed	Length Closed	Height Closed
19.57" (49.7 cm)	24.83" (63 cm)	11.93" (30.3 cm)

Mast Height Extended	Cord Length (Retracted)	Weight
72.85" (185 cm) 0" (0 cm)	13.78" (35 cm) 0" (0 cm)	88.18 lbs. (40 kg)

9470 Remote Area Lighting System Approvals

RoHS (Restriction of Hazardous Substances) Compliant

9470 Remote Area Lighting System Accessories

Cat. #	Description	Sug. Retail
9437	Extension Cord 118 inches (3m)	US\$99.95